

Düker Underground Hydrant Type 304 S, design A

DN 80 PN 16, according to EN 1074-6
Düker etec enamel finish for water

Spigot end as per EN 545, single shut-off, fully enamelled body with automatic drainage and protection against pressurised water, outlet cover with chain, secured obturator linkage, all elastomers and plastic parts according to DVGW W 270, DVGW tested and registered, CE marking as per EN 14399.

Material

- Body, bonnet, DIN outlet coupling, outlet cover: EN-GJS-500-7 (JS 1050)
- Massive obturator linkage, stem X20Cr13
- Stem nut and bonnet nut in special brass
- Obturator – EPDM elastomer

All materials in contact with potable water correspond to the German UBA guidelines

Surface protection

- inside and outside Düker etec enamel according to EN ISO 11177, DEV guideline class III soils

Field of application: Drinking water up to +60 °C

Nominal diameter DN	Nominal pressure PN	Test pressure in bar (water)	
		Body	Seat
80	16	24	17,6

Item no.	Pipe covering m	H	PN	Design	Closing Cover
763787	0,75	670	16	Spigot end	standard
304948	0,75	670	16	Spigot end	self-locking
763788	1,00	890	16	Spigot end	standard
304952	1,00	890	16	Spigot end	self-locking
763789	1,25	1140	16	Spigot end	standard
312791	1,25	1140	16	Spigot end	self-locking
763790	1,50	1390	16	Spigot end	standard
312792	1,50	1390	16	Spigot end	self-locking

Closing cover:

- Standard (cover with chain)
- With self-locking cover



Accessories:

- Operating key



situation 04.20
Subject to modification and error

Düker GmbH
Würzburger Str. 10-16
D-97753 Karlstadt/Main

Tel. +49 9353 791-560
Fax +49 9353 791-8560

Internet: www.dueker.de
E-Mail: sales.fittings-valves@dueker.de