

Düker Service Connection Valve Type 1004

PN 16, GW 336, EN 1074 part 1+2
 Face-to-face dimension EN 16722 : 2015-12, M4
 Düker etec enamel finish for water

Resilient-seated gate valve, internal stem thread with connecting dimension EN 10226-1, inside and outside etec enamel according to the DEV guidelines for class III soils, EN ISO 11177, 12 mm stem square, rubberized wedge, EPDM gaskets as well as plastic parts according to W 270 material approval, DVGW tested and registered.



Material

- Body EN-GJS-500-7 (JS 1050)
- Stem – X20Cr13
- Bonnet, obturator – special brass
- Obturator – special brass entirely vulcanized (elastomer – EPDM)

All materials in contact with potable water correspond to the German UBA guidelines

Surface protection

- Düker etec enamel inside and outside

Field of application: Drinking water up to +60 °C

Nominal diameter DN	Nominal pressure PN	Test pressure in bar (water)	
		Body	Seat
25–50	16	24	17.6

Item no.	DN	Thread
570109	25	1"
570032	32	1 1/4"
570053	40	1 1/2"
570082	50	2"

Upon request:

- inside and outside epoxy blue RAL 5005 according to the GSK guidelines

Operation:

- Stem extension set for connection GW 336
- Operating key