

Düker Tapping Clamp Fig. 88

PN 10/16

Tapping clamp fig. 88 with internal pipe thread for vertical and horizontal drilling

Material

- Body EN-GJS-500-7 (JS 1050)

Surface protection

- inside and outside epoxy black RAL 9005
- inside Düker enamel as per EN ISO 11177 according to the GSK guidelines
- outside bituminous coating

Field of application: Drinking water up to +60 °C



Item no.	Rp
556560	Blind
556561	1
556562	1 1/4
556563	1 1/2
556564	2

Item no.	Rp
558211	Blind
556486	1
556487	1 1/4
556489	1 1/2
556490	2

Listed prices do not include the clapping bands (stainless steel).

Clapping Band (Stainless Steel)

for tapping valves TOP
for tapping clamps fig. 88

Flat clamping band matching cast iron, steel and cement mortar pipe as well as asbestos cement pipe PN 12.5. The clamps come in a set together with the gasket.

Material

- Flat clamping band and bolts:
Stainless steel 1.430, plastic-coated black
- Nuts: 1.4571 with sliding coating
- Spherical washers: 1.4104
- Protection caps: plastics
- Saddle sealing gasket: EPDM



Item no.	DN	Application	Pipe outside Ø mm	Length
791759	80	DI/AC	98 – 101,6	335
791760	80	DICM	106	360
791761	80	Steel	88,9	315
791763	100	DI/steel/AC	114,3 – 124	385
791764	100	DICM	126	415
791765	100	Steel	108	370
791767	125	DI	144 – 148	450
791766	125	DICM/AC	153 – 154	480
791774	125	Steel	139,7	435
791776	150	DI/Steel	168,3 – 174	520
771775	150	DICM/AC	180 – 182	540

Item no.	DN	Application	Pipe outside Ø mm	Length
791777	150	Steel	159	500
791778	175	DI/steel	196 – 200	590
791781	200	DI/steel	219,1 – 226	670
791779	200	DICM/AC	232 – 240	700
791782	225	DI/steel	248 – 252	750
791785	250	DI/steel	273 – 278	825
791783	250	DICM/AC	286 – 296	865
791787	300	AC	352	1.030
791789	300	DI/steel	323,9 – 330,4	990
791788	300	DICM	338	1.010

DI = ductile cast iron
CM = cement mortar
AC = asbestos cement

situation 04.20

Subject to modification and error

Düker GmbH
Würzburger Str. 10-16
D-97753 Karlstadt/Main

Tel. +49 9353 791-560
Fax +49 9353 791-8560

Internet: www.dueker.de
E-Mail: sales.fittings-valves@dueker.de